

# PETRIN A SPIRALE

## IM

Modèle	Capacité de pâte	Capacité de farine	Volume cuve	Dimension cuve	Puissance moteur	Volt	Dimensions P x l x H	Poids KG
	KG	KG	L	Mm	kw			
IM5	5	3	7	237X160	0.37	230/50	540X260X527	33
IM5T	5	3	7	237X160	0.37	400/50	540X260X527	33
IM8M	8	5	10	260X200	0.37	230/50	550X280X555	36
IM8T	8	5	10	260X200	0.37	400/50	550X280X555	36
IM12M	12	8	15	317X210	0.9	230/50	675X350X690	60
IM12T	12	8	15	317X210	0.75	400/50	675X350X690	60
IM12D	12	8	15	317X210	0.6/0.8	400/50	675X350X690	60
IM18M	18	12	20	360X210	0.9	230/50	697X390X690	65
IM18T	18	12	20	360X210	0.75	400/50	697X390X690	65
IM18D	18	12	20	360X210	0.6/0.8	400/50	697X390X690	65
IM25M	25	17	33	400X260	1.1	230/50	762X430X770	95
IM25T	25	17	33	400X260	1.1	400/50	762X430X770	95
IM25D	25	17	33	400X260	1/1.4	400/50	762X430X770	95
IM38M	38	25	40	452X260	1.5	230/50	818X480X770	105
IM38T	38	25	40	452X260	1.5	400/50	818X480X770	105
IM38D	38	25	40	452X260	1.5/2.2	400/50	818X480X770	105
IM44M	44	30	50	500X270	1.5	230/50	842X530X770	110
IM44T	44	30	50	500X270	1.5	400/50	842X530X770	110
IM44D	44	30	50	500X270	1.5/2.2	400/50	842X530X770	110
IM60M	60	40	75	550X370	2.6	230/50	1020X575X1010	250
IM60T	60	40	75	550X370	2.6	400/50	1020X575X1010	250
IM60D	60	40	75	550X370	2.6/3.4	400/50	1020X575X1010	250

M = monophasé    T = triphasé    D = triphasé 2 vitesses

Modèle	Capacité de pâte	Capacité de farine	Volume cuve	Dimension cuve	Puissance moteur	Volt	Dimensions P x l x H	Poids KG
	KG	KG	L	Mm	kw			
IM12AM	12	8	15	317X210	0.9	230/50	690X350X690	80
IM12AT	12	8	15	317X210	0.75	400/50	690X350X690	80
IM12AD	12	8	15	317X210	0.6/0.8	400/50	690X350X690	80
IM18AM	18	12	20	360X210	0.9	230/50	715X390X690	85
IM18AT	18	12	20	360X210	0.75	400/50	715X390X690	85
IM18AD	18	12	20	360X210	0.6/0.8	400/50	715X390X690	85
IM25AM	25	17	33	400X260	1.1	230/50	780X430X770	115
IM25AT	25	17	33	400X260	1.1	400/50	780X430X770	115
IM25AD	25	17	33	400X260	1/1.4	400/50	780X430X770	115
IM38AM	38	25	40	452X260	1.5	230/50	838X480X770	130
IM38AT	38	25	40	452X260	1.5	400/50	838X480X770	130
IM38AD	38	25	40	452X260	1.5/2.2	400/50	838X480X770	130
IM44AM	44	30	50	500X270	1.5	230/50	878X530X770	140
IM44AT	44	30	50	500X270	1.5	400/50	878X530X770	140
IM44AD	44	30	50	500X270	1.5/2.2	400/50	878X530X770	140
IM60AD	60	40	75	550X370	2.6/3.4	400/50	1020X575X770	270

Tête relevable

M = monophasé    T = triphasé    D = triphasé 2 vitesses



ZA de l'Agavon—1 avenue Jean Jaurès—13170 LES PENNES MIRABEAU

04 42 89 16 89—contact@matos-13.com—www.matos-13.com